



## VICTORY GSE



- Highly reliable Deutz / Cummins / Detroit Diesel engine.
- Meets latest EPA norms.
- Walk Away - Protection and Control (Un attended Operation)
- Low Noise level.
- Standard conformance to AHM 933.

The most reliable Aircraft GSE on earth from AIR+ MAK,

Type : Self Propelled  
Capacity : 15000 Pounds  
**Engine** : Deutz / Cummins / Detroit diesel / equivalent diesel engine

### MAIN PLATFORM

Minimum collapsed height : 48 cm (19")  
Maximum height : 355 cm (140")

### FRONT PLATFORM (Bridge)

Minimum collapsed height : 188cm (74")  
Maximum height : 355cm (140")

### LOAD TRANSFER ON PLATFORMS

Mechanism used : Power driven units  
Drive : Through Hydraulic Motors (Forward/Reverse direction)  
Raising / Retraction of PDU's : Through Hydraulic Cylinders

### EMERGENCY SECTION

Source : Hand pump  
Available operations : - Lowering of Main Platform  
- Lowering of Bridge  
- Retraction of Stabiliser Jacks

### SAFETY

All Safety requirements as per AHM 933

### SPECIFICATIONS FOR HYDRAULIC POWER-PACK

Maximum operating pressure : 3000 psi (210 kg/cm<sup>2</sup>)  
Pump Type : Pressure compensated variable displacement axial piston pump  
Coil for DC Valves : 24V DC Coils  
**Propulsion System** : Two infinitely variable speed settings, hydrostatic drive.  
**Propulsion Speed** : 10 km/h  
**Axles** : ITL, UK make, Steerable drive axles  
**Brakes** : Hydraulic Power Assist

### OTHER MODELS

- ☞ Towable Type 15000 pounds capacity (Economical Version)
- ☞ Any Other Non-Standard types as per Customer Requirement

*\* Due to continuous development, the dimensions, layout, configuration and specifications are subject to change without notice.*

*Note : For more details, Please contact us.*

**VICTORY GSE SALES DEPARTMENT**  
JAMEY EKERLING JAMEY@VICTORYGSE.COM  
AL GARDNER ALG@VICTORYGSE.COM

